



adore.
REGENT
SOLID RIGID CORE



CINDERED COBALT



SUMMERSTORM



FAIRBRIGHT OAK



SEASIDE MYRTLE



NORSE COUNTRY BARK




MONARCHX
featuring an attached pad

5.9" x 48.0" nominal plank dimensions
12.0" x 24.0" nominal tile dimensions
4.8 mm total thickness
3.5 mm core gauge
12 mil (0.3mm) wear layer
Class-leading 1.0 mm attached IXPE pad
Industry-leading click down installation
Duramond™ surface enhancement
Orthophthalate-free construction
100% recyclable after use
Planks - 16 planks / 31.51 ft² (nom.)
10 Year Light Commercial Warranty
Lifetime Residential Warranty



SALTED OAK



KNOTTED HEARTWOOD



RIVERBANK GRAY



WHEATON GOLD



SMOKED CYPRESS



MONARCHX
featuring an attached pad

Specifications	Standard	Monarch X Result
Total Thickness	ASTM F-386	4.8mmw/pad
Wear Layer Thickness	ASTM F-410	0.3mm/12 mil
Critical Radiant Flux	ASTM E-648	Class 1
Chemical Resistance	ASTM F-925	No change 24 hours
Static Load Limit	ASTM F-970	1,500 psi
Heat Stability	ASTM F-1514	<8.0 Delta E
Light Stability	ASTM F-1515	<8.0 Delta E
Residual Indentation	ASTM F-1914	<0.002 inch
Size Change	ISO 23999	Pass
Size and Squareness	ASTM F-2421	<0.25%
Static Coefficient of Friction	ASTM D-2047	Meets or exceeds 0.6
Cupping/Curling	ISO 23999	<0.05mm
Impact Sound Transmission (IIC)	ASTM E-492	IIC 63
Airborne Sound Transmission (STC)	ASTM E-90	STC 53
Impact Sound Reduction (ΔIIC)	ASTM E-2179	ΔIIC 24