

Colosseum

Classification	ASTM F 1700-04 Class III, type B Solid Vinyl Floor Tile	
Size	Plank: 4" x 36" / 102 mm x 915 mm Tile: 12" x 24" / 305 mm x 610 mm	
Overall Thickness	1/8" (nominal) / 3.0 mm	
Wearlayer Thickness	20 mil / 0.50 mm	
Construction	Layered plank/tile consisting of wearlayer, film, and backing	
Edge	Square	
Standard Colors	3 standard colors	
Limited Wear Warranty	20-Year Residential / 10-Year Commercial	
Recycled Content	This product contains a minimum of 50% recycled content. Product can be fully recycled post-use.	
Packaging	Plank: 35.95 ft ² (3.34 m ²) per carton 36 pieces per carton 52 cartons per pallet 20 pallets per 20' container	Tile: 35.95 ft ² (3.34 m ²) per carton 18 pieces per carton 60 cartons per pallet 16 pallets per 20' container
Weight Per Carton	38.25 lbs / 17.38 kg	38.13 lbs / 17.33 kg

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

Product Testing

Flammability	ASTM D 2859-06/CPSC FF 1-70	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Smoke Density	ASTM E 662-06	<450
Slip Resistance	ASTM C 1028	Exceeds ADA and OSHA recommendations
Static Load Limit	ASTM F 970	1,500 psi

