

## Hathaway

|                       |  |
|-----------------------|--|
| Classification        | ASTM F 1700-04 Class III, type B Solid Vinyl Floor Tile  |
| Size                  | 6" x 48" / 153 mm x 1220 mm  |
| Overall Thickness     | 1/8" (nominal) / 3.0 mm  |
| Wearlayer Thickness   | 20 mil / 0.50 mm   |
| Construction          | Layered plank consisting of wearlayer, film, and backing   |
| Edge                  | Beveled  |
| Standard Colors       | 6 standard colors  |
| Limited Wear Warranty | 20-Year Residential / 10-Year Commercial   |
| Recycled Content      | This product contains a minimum of 50% recycled content.<br>Product can be fully recycled post-use.                                      |
| Packaging             | 35.95 ft <sup>2</sup> (3.34 m <sup>2</sup> ) per carton<br>18 pieces per carton<br>60 cartons per pallet<br>16 pallets per 20' container |
| Weight Per Carton     | 38.13 lbs / 17.33 kg   |

*Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and adhesive/application recommendations.*

### Product Testing

|                       |                             |                                      |
|-----------------------|-----------------------------|--------------------------------------|
| Flammability          | ASTM D 2859-06/CPSC FF 1-70 | Passed                               |
| Critical Radiant Flux | ASTM E 648-06               | Class I, CRF $\geq 0.45$             |
| Smoke Density         | ASTM E 662-06               | <450                                 |
| Slip Resistance       | ASTM C 1028                 | Exceeds ADA and OSHA recommendations |
| Static Load Limit     | ASTM F 970                  | 1,500 psi                            |

