

American Tile Inc

SPECIFICATIONS



	SLIP GRIP	PREMIUM QUARTZ	SOLID COLORS	NOVA SERIES	PREMIUM MARBLE	PREMIUM WOOD
Colors	5	4	6	43	7	6
Size	12" X 12" (305 mm X 305 mm)					4"x24"
Gauge	1/8 (3.2 mm)					
Packaging	45 pcs (45 sq. Ft; 1.2 sq meters) (63 Lbs Per Ctn)				68 pcs.(45 sq. ft.)	
Composition	Vinyl Composition					
ASTM F 1066	Composition 1, Class 2					
Federal Specification SS-T-31 2b	Type IV. Composition I					
Static load limit	Tested at 325 psi					
Fire resistance* ASTM E 94 75 or less	YES					
Recommended sub floor	Suspended wood concrete, all grade levels					
Warranty	Seven year commercial limited Warranty					

* Fire Resistance: Products are manufactured to have a flame spread rating of less than 75 when tested in accordance with ASTM E 84 Tunnel test.

SEVEN YEARS LIMITED WARRANTY

Vinylasa Warrants that its first quality flooring material is free from manufacturing defects and will replace defective floor covering for a period of up to seven years from the date of purchase in accordance with the conditions set forth below. If a manufacturing defect is found, the dealer who sold your flooring materials should be notified promptly of the defect and supplied with proof of the date of purchase and the amount of flooring purchased.

Inspection by authorized Vinylasa representative may be necessary to verify that a manufacturing defect exists, or you may be required to submit samples for laboratory analysis. Vinylasa will repair defective areas or will supply, at no charge, new Vinylasa materials of the same or similar color, design, and grade for defective areas along with reasonable labor costs for replacement, for a period of up to seven years from the date of purchase.

If replacements is required in accordance with this warranty and the defective material or pattern has been discontinued or is unavailable, Vinylasa reserves the right to select and supply similar Vinylasa replacement material; otherwise, the same material will be supplied for replacement purposes.

This warranty does not include the following:

1. Dissatisfaction due to improper installation, maintenance, or irregularities caused by sub floor irregularities.
2. Reduction in gloss due to use.
3. Damage due to: burns, cuts, gouges, scuffs, scratches, indentations, and other accidents or abuse.
4. Problems due to moisture (including fungus discoloration) alkali or hydrostatic pressure in the sub floor.
5. Color variations from samples or printed illustrations compared to actual production runs.
6. Installing of flooring over particle board, chip wood or pressboard.
7. installation where materials were not installed with the proper adhesive.

This warranty is made solely to the original purchaser of Vinylasa first quality flooring material and is not transferable under any circumstances. This warranty is expressly in lieu of any other express warranty. No representative, employee, or agent of Vinylasa, or any other person, is authorized to assume for Vinylasa any additional liability or responsibility in connection with Vinylasa floor covering except as described above. Implied warranties of merchantability and fitness for a particular purpose are limited to a period of seven

years from the date of purchase. In no event shall Vinylasa be liable for indirect, special, consequential, incidental damages of any kind.